



B.24 SHOTBOLT SOLENOID LOCKING POWER ON



BDC.24 and BAC.24

Application use -

Locking doors, hatches, drawers, or used as positioning stop on production tools. The shotbolt is powered ON to lock. Its internal spring ensures the bolt returns to the unlocked position after the power is switched off.

Maximum radial force: **300kg**

Stroke: **11mm**

Plunger input and output force: **500g**

Standard voltage: **24V DC - 230V AC**

Possible voltages: **12V - 200V DC**

24V - 230V AC (-10%, +5%)

Power: **18W-100% (Permanent service)**

Connection: **DIN 43650-A / ISO4400 Connector**

Return Spring: **Internal**

Protection: **IP54**

Weight: **960g**

Service operating temperature: **-5°C, +40°C**

Temperature rating: **B**

Dimensions (mm): **110x45x90.5**

According to Standards: **NF C 79-300**

Markets: **Automation and Industry**

Factory reference

BDC24 = K.8.458.44.24

BAC24 = K4.8.458.44.24

We reserve the right to alter or amend designs without prior notice.

HE & BS Benson Ltd

1 Laureate Industrial Estate, Exning Road, Newmarket, Suffolk UK CB8 0AR

B24 Rev 3 - 2021

+44(0)1638 663535 — 663130 ✉ sales@bensonsolenoids.co.uk 🌐 www.bensonsolenoids.co.uk

